

Claims

1. A dosing spoon for microtablets with a spoon handle (10) and with a lower part (1) which consists of an even polygon which possesses a border (2) on all sides with exception of one side and whereby the lower part (1) has several rows of individual recesses which are formed in such a way that an individual microtablet fits in each individual recess,
characterized in
that the individual recesses for receiving the microtablets in the lower part (1) of the open-top configured dosing spoon are made of cylindrical bore holes (3) which are configured in the lower part (1) in obliquely offset placed rows and that the borderless side (8) of the lower part (1) is running parallel to the longitudinal axis of the spoon handle (10) which runs in longitudinal direction to the side of the lower part (1) which shows the border which is opposite the borderless side (8) of the lower part (1).
2. A dosing spoon according to claim 1,
characterized in
that the polygon of the lower part (1) is made of a square in form of a parallelogram in which the opposing sides have the same lengths, whereby preferably the small angle (4) between two sides of the parallelogram is between 45° and 90° and whereby one long side (5) of the parallelogram as well as the two shorter sides (6, 7) are provided with a border (2).
3. A dosing spoon according to claim 2,
characterized in
that the border (2) of the two shorter sides (6, 7) of the parallelogram slightly projects over the polygon, for example up to 5 mm vertically.

4. A dosing spoon according to any of the claims 1 to 3, characterized in that the diameter and the depth of the cylindrical bore hole (3) are bigger than the biggest diagonal of a microtablet.
5. A dosing spoon according to any of the claims 1 to 4, characterized in that the diameter and the depth of the cylindrical bore hole (3) are between 1,5 mm and 4,0 mm.
6. A dosing spoon according to any of the claims 1 to 5, characterized in that the correspondence of the cylindrical bore holes (3) in the lower part (1) is close together.
7. A dosing spoon according to any of the claims 1 to 6, characterized in that the total number of the cylindrical bore holes (3) in the lower part (1) corresponds to the quantity of the microtablets to be received, whereby the number of the cylindrical bore holes (3) is from 5 to 100, preferably from 10 to 60.
8. A dosing spoon according to any of the claims 1 to 7, characterized in that on the borderless side (8) of the polygone a zone without bore holes, which has preferably a width up to 1 cm, is configured for facilitating the filling of the cylindrical bore holes (3) with microcapsules.